


# Solenoid valve VZWF-L-M22C-G2-500-E-1P4-6

Part number: 1492133

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                          | Value                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Design                           | Force pilot operated                                                                                                         |
| Type of actuation                | Electric                                                                                                                     |
| Sealing principle                | Soft                                                                                                                         |
| Mounting position                | Solenoid vertical                                                                                                            |
| Type of mounting                 | In-line installation                                                                                                         |
| Connection Process valve         | G2                                                                                                                           |
| Electrical connection            | Type A<br>Plugs<br>To EN 175301-803<br>Square design                                                                         |
| Nominal size                     | 50 mm                                                                                                                        |
| Valve function                   | 2/2-way, closed, monostable                                                                                                  |
| Manual override                  | None                                                                                                                         |
| Flow direction                   | Non-reversible                                                                                                               |
| Medium                           | Compressed air to ISO 8573-1:2010 [7:-:-]<br>Inert gases<br>Mineral oil<br>Water<br>Neutral fluids<br>Other media on request |
| Nominal pressure PN              | 40                                                                                                                           |
| Pressure difference              | 0 MPa                                                                                                                        |
| Pressure difference              | 0 bar                                                                                                                        |
| Pressure difference              | 0 psi                                                                                                                        |
| Characteristic coil data         | 24 V DC: 30.0 W                                                                                                              |
| Permissible voltage fluctuations | +/- 10 %                                                                                                                     |
| Symbol                           | 00992976                                                                                                                     |
| Medium pressure                  | 0 MPa ... 0.6 MPa                                                                                                            |
| Medium pressure                  | 0 bar ... 6 bar                                                                                                              |
| Medium pressure                  | 0 psi ... 87 psi                                                                                                             |
| Max. viscosity                   | 22 mm <sup>2</sup> /s                                                                                                        |
| Media temperature                | -10 °C ... 80 °C                                                                                                             |

| Feature                                               | Value                                              |
|-------------------------------------------------------|----------------------------------------------------|
| Ambient temperature                                   | -10 °C ... 35 °C                                   |
| Leakage rate to EN 12266-1                            | A                                                  |
| Flow rate Kv                                          | 28 m³/h                                            |
| Standard nominal flow rate (standardised to DIN 1343) | 29900 l/min                                        |
| Switching time on                                     | 1220 ms                                            |
| Switching time off                                    | 2140 ms                                            |
| Note on materials                                     | RoHS-compliant                                     |
| LABS (PWIS) conformity                                | VDMA24364 zone III                                 |
| Material housing                                      | Cast brass                                         |
| Material number housing                               | CW617N                                             |
| Material seals                                        | EPDM                                               |
| Material screws                                       | High-alloy stainless steel                         |
| Material number screw                                 | 1.4301                                             |
| Product weight                                        | 6500 g                                             |
| CE mark (see declaration of conformity)               | In accordance with EU Pressure Equipment Directive |
| Degree of protection                                  | IP65                                               |
| Corrosion resistance class CRC                        | 1 - Low corrosion stress                           |