



# Solenoid valve MFH-5/3E-D-3-C

Part number: 151874

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                               | Value                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Valve function                                        | 5/3 exhausted                                                                              |
| Type of actuation                                     | Electric                                                                                   |
| Construction width                                    | 65 mm                                                                                      |
| Standard nominal flow rate (standardised to DIN 1343) | 4600 l/min                                                                                 |
| pneumatic working port                                | Sub-base size 3 to ISO 5599-1<br>G1/2                                                      |
| Operating voltage                                     | Via solenoid coil, must be ordered separately                                              |
| Operating pressure                                    | 0.3 MPa ... 1 MPa                                                                          |
| Operating pressure                                    | 3 bar ... 10 bar                                                                           |
| Design                                                | Piston gate valve                                                                          |
| Type of reset                                         | Mechanical spring                                                                          |
| Maritime classification                               | See certificate                                                                            |
| Certificate issuing authority                         | DNV-TAA000032X                                                                             |
| Degree of protection                                  | IP65                                                                                       |
| Nominal size                                          | 14.5 mm                                                                                    |
| Grid dimension                                        | 71 mm                                                                                      |
| Exhaust-air function                                  | With flow control option                                                                   |
| Sealing principle                                     | Soft                                                                                       |
| Mounting position                                     | optional                                                                                   |
| Conforms to standard                                  | ISO 5599-1                                                                                 |
| Manual override                                       | Detenting via accessory<br>Non-detenting                                                   |
| ISO code                                              | 357                                                                                        |
| Type of piloting                                      | Pilot actuated                                                                             |
| Pilot air supply                                      | Internal                                                                                   |
| Flow direction                                        | Non-reversible                                                                             |
| Symbol                                                | 00991082                                                                                   |
| lap                                                   | Overlap                                                                                    |
| Suitability for vacuum                                | no                                                                                         |
| Switching time off                                    | 78 ms                                                                                      |
| Switching time on                                     | 37 ms                                                                                      |
| Max. positive test pulse with 0 signal                | 2200 µs                                                                                    |
| Max. negative test pulse with 1 signal                | 3700 µs                                                                                    |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required) |

| Feature                      | Value                                                                            |
|------------------------------|----------------------------------------------------------------------------------|
| Vibration resistance         | Transport application test with severity level 1 to FN 942017-4 and EN 60068-2-6 |
| Shock resistance             | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                |
| LABS (PWIS) conformity       | VDMA24364-B1/B2-L                                                                |
| Media temperature            | -10 °C ... 60 °C                                                                 |
| Sound pressure level         | 85 dB(A)                                                                         |
| Ambient temperature          | -5 °C ... 40 °C                                                                  |
| Product weight               | 1040 g                                                                           |
| Electrical connection        | Via F coil, to be ordered separately                                             |
| Type of mounting             | On sub-base<br>Via through-hole and screw                                        |
| Pilot exhaust port 82        | M5                                                                               |
| Pilot exhaust port 84        | M5                                                                               |
| Pneumatic connection, port 1 | Sub-base size 3 to ISO 5599-1                                                    |
| Pneumatic connection, port 2 | Sub-base size 3 to ISO 5599-1                                                    |
| Pneumatic connection, port 3 | Sub-base size 3 to ISO 5599-1                                                    |
| Pneumatic connection, port 4 | Sub-base size 3 to ISO 5599-1                                                    |
| Pneumatic connection, port 5 | Sub-base size 3 to ISO 5599-1                                                    |
| Note on materials            | RoHS-compliant                                                                   |
| Material seals               | HNBR<br>NBR                                                                      |
| Material housing             | Die-cast aluminium                                                               |