

# Sub-base PAML-CP-186-HP3-G114

Part number: 1629296

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                        | Value                                     |
|--------------------------------|-------------------------------------------|
| Size                           | 186                                       |
| Nominal size DN                | 54                                        |
| Series                         | L                                         |
| Operating pressure             | 0 MPa ... 5 MPa                           |
| Operating pressure             | 0 bar ... 50 bar                          |
| Operating medium               | Compressed air to ISO 8573-1:2010 [-:-:-] |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress             |
| LABS (PWIS) conformity         | VDMA24364-B2-L                            |
| Storage temperature            | -10 °C ... 60 °C                          |
| Suitable for use with food     | See supplementary material information    |
| Media temperature              | 5 °C ... 60 °C                            |
| Ambient temperature            | 5 °C ... 60 °C                            |
| Product weight                 | 4600 g                                    |
| Pneumatic connection, port 1   | G1 1/4                                    |
| Pneumatic connection, port 2   | G1 1/4                                    |
| Note on materials              | RoHS-compliant                            |
| Material sub-base              | Wrought aluminium alloy                   |
| Material seals                 | NBR                                       |
| Material screws                | Stainless steel                           |