


# Flat cylinder DZF-40- -P-A-S2

Part number: 164051

FESTO



General operating condition

## Data sheet

Overall data sheet – Individual values depend upon your configuration.

| Feature                                                      | Value                                                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Stroke                                                       | 1 mm ... 320 mm                                                                            |
| Piston diameter                                              | 40 mm<br>Equivalent diameter                                                               |
| Piston rod thread                                            | M8                                                                                         |
| Torsional backlash at piston rod +/-                         | 0.6 deg                                                                                    |
| Cushioning                                                   | Elastic cushioning rings/plates at both ends                                               |
| Mounting position                                            | optional                                                                                   |
| Mode of operation                                            | Double-acting                                                                              |
| Design                                                       | Piston<br>Piston rod                                                                       |
| Position detection                                           | Via proximity switch                                                                       |
| Symbol                                                       | 00991219                                                                                   |
| Variants                                                     | Through piston rod                                                                         |
| Protection against torque/guide                              | Oval piston                                                                                |
| Operating pressure                                           | 0.1 MPa ... 1 MPa                                                                          |
| Operating pressure                                           | 1 bar ... 10 bar                                                                           |
| Operating medium                                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                                       | VDMA24364-B1/B2-L                                                                          |
| Ambient temperature                                          | -20 °C ... 80 °C                                                                           |
| Impact energy in end positions                               | 0.52 J                                                                                     |
| Max. torque for protection against torsion                   | 1 Nm                                                                                       |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 633 N                                                                                      |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 633 N                                                                                      |
| Moving mass for 0 mm stroke                                  | 120 g                                                                                      |
| Additional moving mass per 10 mm stroke                      | 16 g                                                                                       |
| Additional weight per 10 mm stroke                           | 40 g                                                                                       |
| Basic weight for 0 mm stroke                                 | 480 g                                                                                      |
| Type of mounting                                             | Either:<br>Via female thread<br>With accessories                                           |
| Pneumatic connection                                         | G1/8                                                                                       |
| Material cover                                               | Die-cast aluminium                                                                         |

| Feature              | Value                            |
|----------------------|----------------------------------|
| Material seals       | NBR<br>TPE-U(PU)                 |
| Material housing     | Anodised wrought aluminium alloy |
| Material piston seal | NBR                              |
| Material piston rod  | High-alloy steel                 |