


# Pressure regulator LR-1/2-D-7-I-MIDI

Part number: 192315

**FESTO**



General operating condition

## Data sheet

| Feature                                               | Value                                                                                                                |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Size                                                  | Midi                                                                                                                 |
| Series                                                | D                                                                                                                    |
| Actuator lock                                         | Rotary knob with detent                                                                                              |
| Mounting position                                     | optional                                                                                                             |
| Design                                                | Directly actuated diaphragm regulator                                                                                |
| Controller function                                   | Output pressure constant<br>Via primary pressure compensation<br>With secondary venting<br>With return flow function |
| Symbol                                                | 00991558                                                                                                             |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge                                                                                                  |
| Operating pressure                                    | 0 MPa ... 1.6 MPa                                                                                                    |
| Operating pressure                                    | 0 bar ... 16 bar                                                                                                     |
| Pressure regulation range                             | 0.5 bar ... 7 bar                                                                                                    |
| Max. pressure hysteresis                              | 0.02 MPa                                                                                                             |
| Max. pressure hysteresis                              | 0.2 bar                                                                                                              |
| Max. pressure hysteresis                              | 2.9 psi                                                                                                              |
| Standard nominal flow rate (standardised to DIN 1343) | 4000 l/min                                                                                                           |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:4:4]<br>Inert gases                                                             |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required)                           |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L                                                                                                    |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [7:4:4]<br>Inert gases                                                             |
| Media temperature                                     | -10 °C ... 60 °C                                                                                                     |
| Ambient temperature                                   | -10 °C ... 60 °C                                                                                                     |
| Product weight                                        | 720 g                                                                                                                |
| Type of mounting                                      | Front panel mounting<br>In-line installation<br>With accessories                                                     |
| Pneumatic connection, port 1                          | G1/2                                                                                                                 |
| Pneumatic connection, port 2                          | G1/2                                                                                                                 |
| Note on materials                                     | RoHS-compliant                                                                                                       |
| Material sub-base                                     | Die-cast zinc                                                                                                        |
| Material seals                                        | NBR                                                                                                                  |

| Feature          | Value         |
|------------------|---------------|
| Material housing | Die-cast zinc |