

# Spiral plastic tubing PUN-12X2-S-6-SW

Part number: 197616

FESTO



 General operating condition

## Data sheet

| Feature                                  | Value                                           |
|------------------------------------------|-------------------------------------------------|
| Working length                           | 6 m                                             |
| Outside diameter                         | 12 mm                                           |
| Block length                             | 0.98 m                                          |
| Inside diameter                          | 8 mm                                            |
| Winding diameter                         | 95 mm                                           |
| Number of turns                          | 64                                              |
| Temperature-dependent operating pressure | -0.095 MPa ... 1 MPa                            |
| Temperature-dependent operating pressure | -0.95 bar ... 10 bar                            |
| Temperature-dependent operating pressure | -13.775 psi ... 145 psi                         |
| Approval                                 | German Technical Control Board (TÜV)            |
| Certificate issuing authority            | B 013277 0506 00                                |
| Operating medium                         | Compressed air to ISO 8573-1:2010 [7:-:-]       |
| LABS (PWIS) conformity                   | VDMA24364-B2-L                                  |
| Ambient temperature                      | -35 °C ... 60 °C                                |
| Product weight                           | 1300 g                                          |
| Pneumatic connection                     | For push-in connector outside diameter of 12 mm |
| Colour                                   | Black                                           |
| Shore hardness                           | D 52 +/-3                                       |
| Material tubing                          | TPE-U(PU)                                       |