


# Toothed belt axis EGC-120-1000-TB-KF-0H-GK

Part number: 3013368

FESTO



[PDF](#) General operating condition

## Data sheet

| Feature                                                           | Value                                              |
|-------------------------------------------------------------------|----------------------------------------------------|
| Effective diameter of drive pinion                                | 39.79 mm                                           |
| Working stroke                                                    | 1000 mm                                            |
| Size                                                              | 120                                                |
| Stroke reserve                                                    | 0 mm                                               |
| Toothed-belt pitch                                                | 5 mm                                               |
| Mounting position                                                 | optional                                           |
| Guide                                                             | Recirculating ball bearing guide                   |
| Design                                                            | Electromechanical linear axis<br>With toothed belt |
| Type of motor                                                     | Stepper motor<br>Servo motor                       |
| Symbol                                                            | 00991212                                           |
| Max. acceleration                                                 | 50 m/s <sup>2</sup>                                |
| Max. speed                                                        | 5 m/s                                              |
| Repetition accuracy                                               | ±0.08 mm                                           |
| Duty cycle                                                        | 100%                                               |
| LABS (PWIS) conformity                                            | VDMA24364 zone III                                 |
| Degree of protection                                              | IP40                                               |
| Ambient temperature                                               | -10 °C ... 60 °C                                   |
| 2nd moment of area Iy                                             | 4620000 mm <sup>4</sup>                            |
| 2nd moment of area Iz                                             | 5650000 mm <sup>4</sup>                            |
| Max. force Fy                                                     | 6890 N                                             |
| Max. force Fz                                                     | 6890 N                                             |
| Max. force Fy total axis                                          | 6890 N                                             |
| Max. force Fz total axis                                          | 6890 N                                             |
| Fy at theoretical life value of 100 km (only guide consideration) | 25383 N                                            |
| Fz at theoretical life value of 100 km (only guide consideration) | 25383 N                                            |
| Max. idle running transfer resistance                             | 70 N                                               |
| Max. moment Mx                                                    | 144 Nm                                             |
| Max. moment My                                                    | 380 Nm                                             |
| Max. moment Mz                                                    | 380 Nm                                             |
| Max. moment Mx total axis                                         | 144 Nm                                             |
| Max. moment My total axis                                         | 380 Nm                                             |
| Max. moment Mz total axis                                         | 380 Nm                                             |
| Mx at theoretical life value of 100 km (only guide consideration) | 531 Nm                                             |
| My at theoretical life value of 100 km (only guide consideration) | 1400 Nm                                            |

| Feature                                                           | Value                                                                     |
|-------------------------------------------------------------------|---------------------------------------------------------------------------|
| Mz at theoretical life value of 100 km (only guide consideration) | 1400 Nm                                                                   |
| Max. feed force Fx                                                | 800 N                                                                     |
| Torsional mass moment of inertia It                               | 2680000 mm <sup>4</sup>                                                   |
| Mass moment of inertia JH per metre of stroke                     | 0.93 kgcm <sup>2</sup>                                                    |
| Mass moment of inertia JL per kg of working load                  | 3.96 kgcm <sup>2</sup>                                                    |
| Feed constant                                                     | 125 mm/U                                                                  |
| Reference service life                                            | 5000 km                                                                   |
| Material end cap                                                  | Wrought aluminium alloy<br>Anodised                                       |
| Material profile                                                  | Wrought aluminium alloy<br>Anodised                                       |
| Note on materials                                                 | RoHS-compliant                                                            |
| Material drive cover                                              | Wrought aluminium alloy<br>Anodised                                       |
| Material guide slide                                              | Steel                                                                     |
| Material guide rail                                               | Steel                                                                     |
| Material pulleys                                                  | High-alloy stainless steel                                                |
| Material slide                                                    | Wrought aluminium alloy<br>Anodised                                       |
| Material toothed belt clamping piece                              | Stainless steel casting                                                   |
| Material toothed belt                                             | Polychloroprene or nitrile rubber (NBR) with glass cord and nylon coating |