

# Check valve H-1/8-A/I

Part number: 3324

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                               | Value                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Valve function                                        | Non-return function                                                                        |
| Pneumatic connection, port 1                          | G1/8                                                                                       |
| Pneumatic connection, port 2                          | G1/8                                                                                       |
| Type of mounting                                      | In-line installation                                                                       |
| Standard nominal flow rate (standardised to DIN 1343) | 280 l/min                                                                                  |
| Operating pressure                                    | 0.04 MPa ... 0.8 MPa                                                                       |
| Operating pressure                                    | 0.4 bar ... 8 bar                                                                          |
| Ambient temperature                                   | -10 °C ... 60 °C                                                                           |
| Material housing                                      | Brass                                                                                      |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:-:-]                                                  |
| Symbol                                                | 00991455                                                                                   |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required) |
| LABS (PWIS) conformity                                | VDMA24364-B2-L                                                                             |
| Media temperature                                     | -10 °C ... 60 °C                                                                           |
| Product weight                                        | 21 g                                                                                       |
| Material seals                                        | NBR                                                                                        |