


Parallel gripper HGPL-40-20-A-B

Part number: 3361487

FESTO



 General operating condition

Data sheet

Feature	Value
Size	40
Stroke per gripper jaws	20 mm
Max. replacement accuracy	<0.2 mm
Max. angular gripper jaw backlash ax, ay	<0.2 deg
Max. gripper jaw backlash Sz	<0.05 mm
Rotationally symmetrical	≤0.2 mm
Repetition accuracy, gripper	<0.03 mm
Number of gripper jaws	2
Drive system	Pneumatic
Mounting position	optional
Mode of operation	Double-acting
Gripper function	Parallel
Gripper force back-up	None
Design	Twin piston Guidance Piston gate valve T-shape Rack and pinion
Position detection	Via proximity switch
Symbol	00991894
Operating pressure	3 bar ... 8 bar
Max. operating frequency of gripper	<1 Hz
Min. opening time at 0.6 MPa (6 bar, 87 psi)	190 ms
Min. closing time at 0.6 MPa (6 bar, 87 psi)	180 ms
Max. mass per external gripper finger	420 g
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	5 °C ... 60 °C
Total gripping force, opening, 0.6 MPa (6bar, 87 psi)	1038 N
Total gripping force, closing, 0.6 MPa (6bar, 87 psi)	1216 N
Gripper force per gripper jaw, opening, 0.6 MPa (6 bar, 87 psi)	519 N
Gripper force per gripper jaw, closing, 0.6 MPa (6 bar, 87 psi)	608 N
Mass moment of inertia	27.6 kgcm ²

Feature	Value
Max. force on gripper jaw Fz static	2500 N
Max. torque at gripper Mx static	125 Nm
Max. torque at gripper My static	80 Nm
Max. torque at gripper Mz static	100 Nm
Lubrication interval for guide components	5 MioCyc
Product weight	2560 g
Type of mounting	Via female thread and centring sleeve Via through-hole and centring sleeve
Pneumatic connection	M5
Note on materials	RoHS-compliant
Material housing	Smooth-anodised wrought aluminium alloy
Material gripper jaws	Hardened steel