


# Fine filter LFMB-3/4-D-MAXI-DA

Part number: 532825

**FESTO**



 General operating condition

## Data sheet

| Feature                                     | Value                                                    |
|---------------------------------------------|----------------------------------------------------------|
| Series                                      | D                                                        |
| Size                                        | Maxi                                                     |
| Design                                      | Fibre filter                                             |
| Grade of filtration                         | 1 µm                                                     |
| Condensate drain                            | Manually rotating                                        |
| Symbol                                      | 00991543                                                 |
| Operating pressure                          | 0.1 MPa ... 1.6 MPa                                      |
| Operating pressure                          | 1 bar ... 16 bar                                         |
| Operating pressure                          | 14.5 psi ... 232 psi                                     |
| Operating medium                            | Compressed air to ISO 8573-1:2010 [6:4:4]<br>Inert gases |
| Air purity class at output                  | Compressed air to ISO 8573-1:2010 [5:4:3]<br>Inert gases |
| Max. standard flow rate for clean air class | 2220 l/min                                               |
| Min. standard flow rate for clean air class | 750 l/min                                                |
| Filter efficiency                           | 99.99 %                                                  |
| Max. condensate volume                      | 80 ml                                                    |
| Bowl guard                                  | Metal bowl guard                                         |
| Corrosion resistance class CRC              | 2 - Moderate corrosion stress                            |
| LABS (PWIS) conformity                      | VDMA24364-B1/B2-L                                        |
| Media temperature                           | 1.5 °C ... 60 °C                                         |
| Ambient temperature                         | -10 °C ... 60 °C                                         |
| Storage temperature                         | -10 °C ... 60 °C                                         |
| Filter efficiency, fine particles           | 99 %                                                     |
| Residual oil content                        | 0.5 mg/m <sup>3</sup>                                    |
| Filter efficiency, oil aerosol              | 90 %                                                     |
| Differential pressure display               | Visual display                                           |
| Type of mounting                            | Either:<br>In-line installation<br>With accessories      |
| Mounting position                           | Vertical +/-5°                                           |
| Pneumatic connection, port 1                | G3/4                                                     |
| Pneumatic connection, port 2                | G3/4                                                     |

| Feature           | Value              |
|-------------------|--------------------|
| Material housing  | Die-cast zinc      |
| Material filter   | Borosilicate fibre |
| Material bowl     | PC                 |
| Note on materials | RoHS-compliant     |
| Product weight    | 1340 g             |