


# Solenoid valve VSVA-B-M52-AH-A1-1R5L

Part number: 534555

**FESTO**



[General operating condition](#)

## Data sheet

| Feature                                               | Value                                                                     |
|-------------------------------------------------------|---------------------------------------------------------------------------|
| Valve function                                        | 5/2-way, monostable                                                       |
| Type of actuation                                     | Electric                                                                  |
| Construction width                                    | 26 mm                                                                     |
| Standard nominal flow rate (standardised to DIN 1343) | 1100 l/min                                                                |
| pneumatic working port                                | Sub-base size 26 mm to ISO 15407-1                                        |
| Operating voltage                                     | 24V DC                                                                    |
| Operating pressure                                    | 0.3 MPa ... 0.8 MPa                                                       |
| Operating pressure                                    | 3 bar ... 8 bar                                                           |
| Design                                                | Piston gate valve                                                         |
| Type of reset                                         | Pneumatic spring                                                          |
| Approval                                              | RCM trademark<br>c UL us - Recognized (OL)                                |
| CE mark (see declaration of conformity)               | To EU EMC Directive                                                       |
| UKCA marking (see declaration of conformity)          | To UK instructions for EMC<br>To UK RoHS instructions                     |
| Degree of protection                                  | IP65<br>NEMA 4                                                            |
| Nominal size                                          | 9 mm                                                                      |
| Grid dimension                                        | 27 mm                                                                     |
| Exhaust-air function                                  | With flow control option<br>Via throttle plate<br>Via individual sub-base |
| Sealing principle                                     | Soft                                                                      |
| Mounting position                                     | optional                                                                  |
| Conforms to standard                                  | ISO 15407-1                                                               |
| Manual override                                       | Non-detenting                                                             |
| Type of piloting                                      | Pilot actuated                                                            |
| Pilot air supply                                      | Internal                                                                  |
| Flow direction                                        | Non-reversible                                                            |
| Symbol                                                | 00991049                                                                  |
| lap                                                   | Overlap                                                                   |
| Reverse polarity protection                           | For all electrical connections                                            |
| Additional functions                                  | Holding current reduction<br>Safety shut-off                              |
| Signal status display                                 | LED                                                                       |
| b value                                               | 0.25                                                                      |
| C value                                               | 4.5 l/sbar                                                                |

| Feature                                        | Value                                                                                      |
|------------------------------------------------|--------------------------------------------------------------------------------------------|
| Flow rate of valve                             | 1400 l/min                                                                                 |
| Flow rate of valve on individual sub-base      | 1100 l/min                                                                                 |
| Flow rate of pneumatically interlinked valve   | 1100 l/min                                                                                 |
| Switching time off                             | 40 ms                                                                                      |
| Switching time on                              | 25 ms                                                                                      |
| Duty cycle                                     | 100%                                                                                       |
| Max. positive test pulse with 0 signal         | 400 µs                                                                                     |
| Max. negative test pulse with 1 signal         | 100 µs                                                                                     |
| Nominal pick-up current per solenoid coil      | 110 mA up to 20 ms                                                                         |
| Nominal current with current reduction         | 30 mA after 20 ms                                                                          |
| Characteristic coil data                       | 24 V DC: low-current phase 1.0 W, high-current phase 2.4 W                                 |
| Permissible voltage fluctuations               | +/- 10 %                                                                                   |
| Operating medium                               | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium             | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance                           | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6           |
| Shock resistance                               | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                          |
| Corrosion resistance class CRC                 | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                         | VDMA24364-B1/B2-L                                                                          |
| Media temperature                              | -5 °C ... 50 °C                                                                            |
| Relative air humidity                          | 0 - 90%                                                                                    |
| Protection against direct and indirect contact | PELV                                                                                       |
| Pilot medium                                   | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Ambient temperature                            | -5 °C ... 50 °C                                                                            |
| Max. tightening torque for valve mounting      | 1.8 Nm ... 2.2 Nm                                                                          |
| Product weight                                 | 270 g                                                                                      |
| Electrical connection                          | 3-pin<br>M12x1<br>Central plug<br>Round design                                             |
| Type of mounting                               | On sub-base<br>Via through-hole and screw                                                  |
| Note on materials                              | RoHS-compliant                                                                             |
| Material seals                                 | FPM<br>HNBR<br>NBR                                                                         |
| Material housing                               | Die-cast aluminium                                                                         |