



# Solenoid valve VMPA2-M1H-D-PI

Part number: 537960

**FESTO**



[PDF](#) General operating condition

## Data sheet

| Feature                                               | Value                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Valve function                                        | 2x2/2-way, monostable, closed                                                              |
| Type of actuation                                     | Electric                                                                                   |
| Valve size                                            | 20 mm                                                                                      |
| Standard nominal flow rate (standardised to DIN 1343) | 650 l/min ... 840 l/min                                                                    |
| Operating voltage                                     | 24V DC                                                                                     |
| Operating pressure                                    | 0.3 MPa ... 1 MPa                                                                          |
| Operating pressure                                    | 3 bar ... 10 bar                                                                           |
| Design                                                | Piston gate valve                                                                          |
| Type of reset                                         | Pneumatic spring                                                                           |
| Approval                                              | c UL us - Recognized (OL)                                                                  |
| Degree of protection                                  | IP65<br>To IEC 60529                                                                       |
| Sealing principle                                     | Soft                                                                                       |
| Mounting position                                     | optional                                                                                   |
| Manual override                                       | Detenting<br>Non-detenting                                                                 |
| Type of piloting                                      | Pilot actuated                                                                             |
| Flow direction                                        | Non-reversible                                                                             |
| Symbol                                                | 00991803                                                                                   |
| lap                                                   | Overlap                                                                                    |
| Signal status display                                 | yes                                                                                        |
| Pilot pressure                                        | 0.3 MPa ... 0.8 MPa                                                                        |
| Pilot pressure                                        | 3 bar ... 8 bar                                                                            |
| Suitability for vacuum                                | no                                                                                         |
| Note on standard nominal flow rate                    | MPA-L: 840 l/min<br>MPA-S: 650 l/min                                                       |
| Standard nominal flow rate with QS-8                  | 650 l/min                                                                                  |
| Standard nominal flow rate with QS-10                 | 840 l/min                                                                                  |
| Switching time off                                    | 25 ms                                                                                      |
| Switching time on                                     | 7 ms                                                                                       |
| Max. positive test pulse with 0 signal                | 400 µs                                                                                     |
| Max. negative test pulse with 1 signal                | 900 µs                                                                                     |
| Permissible voltage fluctuations                      | +/- 25%                                                                                    |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required) |

| Feature                                   | Value                                                                            |
|-------------------------------------------|----------------------------------------------------------------------------------|
| Vibration resistance                      | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6 |
| Shock resistance                          | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                |
| Corrosion resistance class CRC            | 1 - Low corrosion stress                                                         |
| LABS (PWIS) conformity                    | VDMA24364-B1/B2-L                                                                |
| Storage temperature                       | -20 °C ... 40 °C                                                                 |
| Media temperature                         | -5 °C ... 50 °C                                                                  |
| Relative air humidity                     | Max. 90% at 40°C                                                                 |
| Ambient temperature                       | -5 °C ... 50 °C                                                                  |
| Max. tightening torque for valve mounting | 0.65 Nm                                                                          |
| Product weight                            | 100 g                                                                            |
| Type of mounting                          | With through-hole                                                                |
| Note on materials                         | RoHS-compliant                                                                   |
| Material seals                            | NBR                                                                              |
| Material housing                          | Die-cast aluminium                                                               |