


Proximity sensor SIEN-M12NB-PS-K-L-PA

Part number: 538329

FESTO



General operating condition

Data sheet

| Feature | Value |
|--|--|
| Design | Round |
| Conforms to standard | EN 60947-5-2 |
| Symbol | 00991702 |
| Approval | RCM trademark c UL us listed (OL) |
| CE mark (see declaration of conformity) | To EU EMC Directive To EU Low Voltage Directive In accordance with EU RoHS Directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC To UK RoHS instructions To UK regulations for electrical equipment |
| Measuring principle | Inductive |
| Rated operating distance | 4 mm |
| Assured operating distance | 3.24 mm |
| Reduction factors | Aluminium = 0.35 - 0.5 Stainless steel St 18/8 = 0.6 - 1.0 Copper = 0.25 - 0.45 Brass = 0.35 - 0.5 Steel St 37 = 1.0 |
| Ambient temperature | -25 °C ... 70 °C |
| Repetition accuracy | 0.08 mm |
| Switching output | PNP |
| Switching element function | N/O contact |
| Hysteresis | 0.12 mm ... 0.6 mm |
| Max. switching frequency DC | 2000 Hz |
| Max. output current | 200 mA |
| Voltage drop | ≤1.8 V |
| Short circuit current rating | Pulsed |
| Operational voltage range DC | 10 V ... 30 V |
| Residual ripple | 10 % |
| No-load supply current | ≤15 mA |
| Reverse polarity protection | For all electrical connections |
| Electrical connection | 3-wire Cable |
| Cable length | 2.5 m |
| Material cable sheath | PVC |
| Material insulating sheath | PVC |
| Size | M12 |

| Feature | Value |
|---|--------------------------------|
| Type of mounting | Via lock nut |
| Tightening torque | 1 Nm |
| Mounting type | Not flush |
| Product weight | 113 g |
| Material housing | PA-reinforced |
| Switching status indication | Yellow LED |
| Ambient temperature with moving cable | 0 °C ... 70 °C |
| Degree of protection | IP65 IP67 |
| Corrosion resistance class CRC | 4 - Very high corrosion stress |
| Additional information for sensor selection | with standard sensing distance |
| Electrical output | PNP |
| Selection of sensor design | Polyamide housing |