



Electric cylinder EPCC-BS-32-

Part number: 5428849

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Size	32
Stroke	25 mm ... 200 mm
Stroke reserve	0 mm
Piston rod thread	M8
Reversing backlash theoretical	100 µm
Spindle diameter	8 mm
Spindle pitch	3 mm/U ... 8 mm/U
Torsional backlash at piston rod +/-	1 deg
Mounting position	optional
Piston-rod end	Male thread Female thread
Type of motor	Stepper motor Servo motor
Position detection	Via proximity switch
Design	Electric cylinder With ball screw drive
Spindle type	Ball screw drive
Symbol	00991941
Protection against torque/guide	With plain-bearing guide
Max. acceleration	5 m/s ² ... 15 m/s ²
Max. rotational speed	3750 rpm
Max. speed	0.188 m/s ... 0.5 m/s
Max. homing speed	0.01 m/s
Repetition accuracy	±0.02 mm
Duty cycle	100%
Corrosion resistance class CRC	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Suitability for the production of Li-ion batteries	Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni
Cleanroom class	Class 9 according to ISO 14644-1
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 95% Non-condensing
Degree of protection	IP40
Ambient temperature	0 °C ... 60 °C

Feature	Value
Impact energy in end positions	0.0036 J
Max. drive torque	0.15 Nm ... 0.3 Nm
Max. moment Mx	0 Nm
Max. moment My	1.5 Nm
Max. moment Mz	1.5 Nm
Max. radial force at drive shaft	75 N
Max. feed force Fx	150 N
Frictional torque independent of load	0.065 Nm ... 0.095 Nm
Reference value effective load, horizontal	24 kg
Reference value effective load, vertical	12 kg
Mass moment of inertia JH per metre of stroke	0.0256 kgcm ² ... 0.0311 kgcm ²
Mass moment of inertia JL per kg of working load	0.0023 kgcm ² ... 0.0162 kgcm ²
Mass moment of inertia JO	0.0042 kgcm ² ... 0.0055 kgcm ²
Maintenance interval	Life-time lubrication
Moving mass for 0 mm stroke	98 g ... 268 g
Additional moving mass per 10 mm stroke	3.3 g ... 11.2 g
Basic weight for 0 mm stroke	225 g ... 838 g
Additional weight per 10 mm stroke	24 g ... 32 g
Type of mounting	Via female thread With accessories
Note on materials	RoHS-compliant
Material housing	Smooth anodised
Material piston rod	High-alloy stainless steel
Material spindle nut	Steel
Material spindle	Rolled steel