

Connecting cable NEBV-M12G8-KD-3-M12G4

Part number: 547888

FESTO



 General operating condition

Data sheet

Feature	Value
Conforms to standard	DIN 47100 EN 61076-2-101
Design	Y-distributor with cables on both sides
Distribution	1 to 2
Additional functions	Distribution of the analogue inputs and outputs of a proportional pressure regulator
Cable designation	Without inscription label holder
Type of mounting	Via through-hole for M3 screw
Electrical connection 1, function	Field device side
Electrical connection 1, design	Round
Electrical connection 1, connection type	Socket
Electrical connection 1, cable outlet	Straight
Electrical connection 1, connector system	M12x1, A-coded to EN 61076-2-101
Electrical connection 1, number of connections/cores	8
Electrical connection 1, used connections/cores	5
Electrical connection 1, type of mounting	Screw-type lock
Electrical connection 1, connection pattern	00992265
Electrical connection 2, function	Controller side
Electrical connection 2, design	Round
Electrical connection 2, connection type	Plugs
Electrical connection 2, cable outlet	Straight
Electrical connection 2, connector system	M12x1, A-coded to EN 61076-2-101
Electrical connection 2, number of connections/cores	4
Electrical connection 2, used connections/cores	4
Electrical connection 2, type of mounting	Screw-type lock
Electrical connection 2, connection pattern	00995386
Electrical connection 3, function	Controller side
Electrical connection 3, design	Round
Electrical connection 3, connection type	Plugs
Electrical connection 3, cable outlet	Straight
Electrical connection 3, connector system	M12x1, A-coded to EN 61076-2-101
Electrical connection 3, number of connections/cores	4
Electrical connection 3, used connections/cores	3
Electrical connection 3, type of mounting	Screw-type lock
Electrical connection 3, connection pattern	00995635
Operational voltage range DC	0 V ... 30 V

Feature	Value
Operational voltage range AC	0 V ... 30 V
Current rating at 40° C	2 A
Immunity to surge	0.8 kV
Shielding	yes
Cable length 1	2.5 m
Cable length 2	0.5 m
Cable characteristic	Standard
Bending radius 1, fixed cable installation	≥33 mm
Min. bending radius with free moving insert 1	≥66 mm
Bending radius 2, fixed cable installation	≥33 mm
Min. bending radius with free moving insert 2	≥66 mm
Cable diameter 1	6.3 mm
Tolerance for cable diameter 1	± 0.2 mm
Cable diameter 2	6.3 mm
Tolerance for cable diameter 2	± 0.2 mm
Cable structure	8 x 0.25 mm ²
Nominal cross section conductor	0.25 mm ²
Degree of protection	IP67
Note on degree of protection	In assembled state
Ambient temperature	-25 °C ... 80 °C
Ambient temperature with moving cable	-5 °C ... 80 °C
CE mark (see declaration of conformity)	In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
LABS (PWIS) conformity	VDMA24364-B2-L
Note on materials	RoHS-compliant Free of halogen
Pollution degree	3
Corrosion resistance class CRC	2 - Moderate corrosion stress
Material cable sheath	TPE-U(PUR)
Cable sheath colour	Grey
Material housing	TPE-U(PUR)
Housing colour	Black
Material screw-type lock	Nickel-plated brass
Material seals	NBR
Material electrical contact	Brass, nickel-plated and gold-plated
Material insulating sheath	PP