


Ball screw axis EGC-70- -BS-KF

Part number: 556807



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

| Feature | Value |
|---|--|
| Working stroke | 50 mm ... 1000 mm |
| Size | 70 |
| Spindle diameter | 12 mm |
| Spindle pitch | 10 mm/U |
| Mounting position | optional |
| Guide | Recirculating ball bearing guide |
| Design | Electromechanical linear axis With ball screw |
| Type of motor | Stepper motor Servo motor |
| Spindle type | Ball screw |
| Functional principle of measuring system | Incremental |
| Max. acceleration | 15 m/s ² |
| Max. speed | 0.5 m/s |
| Repetition accuracy | ±0.02 mm |
| Duty cycle | 100% |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Degree of protection | IP40 |
| Ambient temperature | -10 °C ... 60 °C |
| 2nd moment of area Iy | 419000 mm ⁴ |
| 2nd moment of area Iz | 578000 mm ⁴ |
| Max. force Fy | 1850 N |
| Max. force Fz | 1850 N |
| Max. force Fy total axis | 1850 N |
| Max. force Fz total axis | 1850 N |
| Fy at theoretical life value of 100 km (only guide consideration) | 6815 N |
| Fz at theoretical life value of 100 km (only guide consideration) | 6815 N |
| Max. moment Mx | 16 Nm |
| Max. moment My | 51 Nm ... 132 Nm |
| Max. moment Mz | 51 Nm ... 132 Nm |
| Max. moment Mx total axis | 16 Nm |
| Max. moment My total axis | 51 Nm ... 132 Nm |
| Max. moment Mz total axis | 51 Nm ... 132 Nm |
| Mx at theoretical life value of 100 km (only guide consideration) | 59 Nm |
| My at theoretical life value of 100 km (only guide consideration) | 188 Nm ... 486 Nm |

| Feature | Value |
|---|-------------------------------------|
| Mz at theoretical life value of 100 km (only guide consideration) | 188 Nm ... 486 Nm |
| Max. radial force at drive shaft | 220 N |
| Max. feed force Fx | 400 N |
| Torsional mass moment of inertia It | 88000 mm ⁴ |
| Mass moment of inertia JH per metre of stroke | 0.142 kgcm ² |
| Feed constant | 10 mm/U |
| Reference service life | 5000 km |
| Material end cap | Wrought aluminium alloy Anodised |
| Material driver | Wrought aluminium alloy Anodised |
| Material profile | Wrought aluminium alloy Anodised |
| Note on materials | RoHS-compliant |
| Material drive cover | Wrought aluminium alloy Anodised |
| Material guide slide | Steel |
| Material guide rail | Steel |
| Material slide | Wrought aluminium alloy Anodised |
| Material spindle nut | Steel |
| Material spindle | Steel |