


# Radial gripper HGRT-50-A-G2

Part number: 563915

FESTO



 General operating condition

## Data sheet

Feature	Value
Size	50
Max. replacement accuracy	$\leq 0.2$ mm
Max. angular gripper jaw backlash ax, ay	$\leq 0.1$ deg
Max. opening angle	180 deg
Rotationally symmetrical	$\leq 0.2$ mm
Repetition accuracy, gripper	$\leq 0.02$ mm
Number of gripper jaws	2
Mounting position	optional
Mode of operation	Double-acting
Gripper function	Radial
Gripper force back-up	During closing
Design	Force pilot operated motion sequence
Position detection	Via proximity switch Via inductive sensors
Symbol	00991895
Operating pressure	4 bar ... 8 bar
Max. operating frequency of gripper	$\leq 2$ Hz
Min. opening time at 0.6 MPa (6 bar, 87 psi)	490 ms
Min. closing time at 0.6 MPa (6 bar, 87 psi)	355 ms
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Corrosion resistance class CRC	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	5 °C ... 60 °C
Mass moment of inertia	47.7 kgcm <sup>2</sup>
Max. force on gripper jaw Fz static	1200 N
Max. torque at gripper My static	35 Nm
Max. torque at gripper Mz static	10 Nm
Lubrication interval for guide components	10 MioCyc
Product weight	3500 g
Type of mounting	Via female thread and centring sleeve
Pneumatic connection	G1/8
Note on materials	RoHS-compliant
Material housing	Smooth-anodised wrought aluminium alloy
Material gripper jaws	Hardened steel