


Filter regulator MS9-LFR-G-D7-CUV-AG-BAR-AS

Part number: 564121

FESTO



General operating condition

Data sheet

| Feature | Value |
|---|--|
| Size | 9 |
| Series | MS |
| Actuator lock | can be closed with accessories |
| Mounting position | Vertical +/-5° |
| Grade of filtration | 5 µm |
| Condensate drain | Fully automatic |
| Design | Piloted filter diaphragm regulator |
| Max. condensate volume | 220 ml |
| Controller function | Output pressure constant Via primary pressure compensation With secondary venting With return flow function |
| Degree of condensate separation | >75 % |
| Symbol | 00991587 |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge |
| Operating pressure | 2 bar ... 12 bar |
| Pressure regulation range | 0.5 bar ... 12 bar |
| Max. pressure hysteresis | 0.4 bar |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:-] Inert gases |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | 5 °C ... 60 °C |
| Air purity class at output | Compressed air to ISO 8573-1:2010 [6:4:4] |
| Media temperature | -10 °C ... 60 °C |
| Ambient temperature | -10 °C ... 60 °C |
| Pore size | 5 µm |
| Product weight | 2400 g |
| Type of mounting | Either: In-line installation With accessories |
| Material covering | PA-reinforced |
| Material spin disc | POM |
| Material filter carrier | POM |
| Note on materials | RoHS-compliant |
| Material sub-base | Die-cast aluminium |

| Feature | Value |
|---------------------------|---------------------------------------|
| Material mounting bracket | Die-cast aluminium |
| Material filter | PE |
| Material housing | Die-cast aluminium |
| Material module connector | Die-cast aluminium |
| Material membrane | NBR |
| Material bowl | Wrought aluminium alloy |
| Material cup seal | NBR |
| Material screen | PA |
| Material separating plate | POM |
| Material valve stem | Wrought aluminium alloy NBR POM |