


# Branching module MS9-FRM-NG-VS-Y

Part number: 564150

FESTO



 General operating condition

## Data sheet

| Feature                            | Value                                                                       |
|------------------------------------|-----------------------------------------------------------------------------|
| Size                               | 9                                                                           |
| Series                             | MS                                                                          |
| Mounting position                  | optional                                                                    |
| Design                             | Branching module                                                            |
| Symbol                             | 00991510                                                                    |
| Operating pressure                 | 0 bar ... 12 bar                                                            |
| Operational voltage range AC       | 0 V ... 250 V                                                               |
| Operational voltage range DC       | 0 V ... 125 V                                                               |
| Operating medium                   | Compressed air to ISO 8573-1:2010 [7:4:4]                                   |
| Note on operating and pilot medium | Lubricated operation possible                                               |
| Corrosion resistance class CRC     | 2 - Moderate corrosion stress                                               |
| LABS (PWIS) conformity             | VDMA24364-B2-L                                                              |
| Storage temperature                | -10 °C ... 60 °C                                                            |
| Media temperature                  | -10 °C ... 60 °C                                                            |
| Ambient temperature                | -10 °C ... 60 °C                                                            |
| Product weight                     | 1100 g                                                                      |
| Type of mounting                   | Either:<br>Front panel mounting<br>In-line installation<br>With accessories |
| Pneumatic connection, port 3       | 1 NPT                                                                       |
| Pneumatic connection, port 4       | 1 NPT                                                                       |
| Material covering                  | PA-reinforced                                                               |
| Note on materials                  | RoHS-compliant                                                              |
| Material sub-base                  | Die-cast aluminium                                                          |
| Material mounting bracket          | Die-cast aluminium                                                          |
| Material housing                   | Die-cast aluminium                                                          |
| Material module connector          | Die-cast aluminium                                                          |