


# Manifold rail VABM-L1-14W-G14-4-GR

Part number: 573500

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                            | Value                                                                                                                                                    |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Grid dimension                                     | 16 mm                                                                                                                                                    |
| Mounting position                                  | optional                                                                                                                                                 |
| Max. number of valve positions                     | 4                                                                                                                                                        |
| Approval                                           | c UL us - Recognized (OL)                                                                                                                                |
| Corrosion resistance class CRC                     | 2 - Moderate corrosion stress                                                                                                                            |
| LABS (PWIS) conformity                             | VDMA24364-B1/B2-L                                                                                                                                        |
| Suitability for the production of Li-ion batteries | Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni |
| Cleanroom class                                    | Class 6 according to ISO 14644-1                                                                                                                         |
| Storage temperature                                | -20 °C ... 60 °C                                                                                                                                         |
| Product weight                                     | 839 g                                                                                                                                                    |
| Pilot air port 12/14                               | M5                                                                                                                                                       |
| Pilot exhaust port 82/84                           | M5                                                                                                                                                       |
| Pneumatic connection, port 1                       | G1/4                                                                                                                                                     |
| Pneumatic connection, port 2                       | G1/8                                                                                                                                                     |
| Pneumatic connection, port 3                       | G1/4                                                                                                                                                     |
| Pneumatic connection, port 4                       | G1/8                                                                                                                                                     |
| Pneumatic connection, port 5                       | G1/4                                                                                                                                                     |
| Note on materials                                  | RoHS-compliant                                                                                                                                           |
| Material manifold rail                             | Wrought aluminium alloy                                                                                                                                  |