


# One-way flow control valve VFOH-LE-A-G14-Q8

Part number: 578800

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                                                       | Value                                                                                      |
|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Valve function                                                                | Exhaust air one-way flow control function                                                  |
| Pneumatic connection, port 1                                                  | QS-8                                                                                       |
| Pneumatic connection, port 2                                                  | G1/4                                                                                       |
| Type of actuation                                                             | Manual                                                                                     |
| Adjustment component                                                          | External hex                                                                               |
| Type of mounting                                                              | Screw-in                                                                                   |
| Standard nominal flow rate in flow control direction                          | 530 l/min                                                                                  |
| Standard nominal flow rate in blocked direction                               | 402 l/min ... 578 l/min                                                                    |
| Ambient temperature                                                           | 0 °C ... 150 °C                                                                            |
| Mounting position                                                             | optional                                                                                   |
| Symbol                                                                        | 00991452                                                                                   |
| Operating pressure complete temperature range                                 | 0.2 bar ... 10 bar                                                                         |
| Standard flow rate in flow control direction 0.6-10 MPa (6-10 bar, 87-10 psi) | 720 l/min                                                                                  |
| Standard flow rate in non-return direction 0.6-10 MPa (6-10 bar, 87-10 psi)   | 610 l/min ... 760 l/min                                                                    |
| Operating medium                                                              | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                                            | Lubricated operation possible (in which case lubricated operation will always be required) |
| LABS (PWIS) conformity                                                        | VDMA24364-B2-L                                                                             |
| Storage temperature                                                           | -10 °C ... 150 °C                                                                          |
| Media temperature                                                             | 0 °C ... 150 °C                                                                            |
| Nominal torque                                                                | 5 Nm                                                                                       |
| Tolerance for nominal tightening torque                                       | ± 10%                                                                                      |
| Product weight                                                                | 37 g                                                                                       |
| Note on materials                                                             | RoHS-compliant                                                                             |
| Material seals                                                                | FPM                                                                                        |
| Material hollow bolt                                                          | Wrought aluminium alloy                                                                    |
| Material release ring                                                         | Nickel-plated brass                                                                        |
| Material adjusting screw                                                      | High-alloy stainless steel                                                                 |

| Feature                 | Value                  |
|-------------------------|------------------------|
| Material swivel fitting | Brass<br>Nickel-plated |