


# Elbow quick connector LCK-1/8-PK-6-KU

Part number: 6260

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                       | Value                                                                                      |
|-----------------------------------------------|--------------------------------------------------------------------------------------------|
| Nominal size                                  | 5.3 mm                                                                                     |
| Type of seal on screwed plug                  | Sealing edge                                                                               |
| Mounting position                             | optional                                                                                   |
| Design                                        | L-shape                                                                                    |
| Size of pack                                  | 10                                                                                         |
| Operating pressure complete temperature range | -0.095 MPa ... 1 MPa                                                                       |
| Operating pressure complete temperature range | -0.95 bar ... 10 bar                                                                       |
| Operating pressure complete temperature range | -13.775 psi ... 145 psi                                                                    |
| Operating medium                              | Compressed air to ISO 8573-1:2010 [7:-:-]                                                  |
| Note on operating and pilot medium            | Lubricated operation possible                                                              |
| Corrosion resistance class CRC                | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                        | VDMA24364-B1/B2-L                                                                          |
| Ambient temperature                           | -10 °C ... 60 °C                                                                           |
| Pneumatic connection, port 1                  | Male thread G1/8                                                                           |
| Pneumatic connection, port 2                  | For tubing outside diameter of 8 mm<br>For barbed fitting inside diameter of 6 mm with nut |
| Material union nut                            | POM                                                                                        |
| Note on materials                             | RoHS-compliant                                                                             |
| Material hollow bolt                          | Wrought aluminium alloy, anodised                                                          |
| Material swivel fitting                       | POM                                                                                        |