


# Solenoid valve VSVA-B-T32U-AZTR-D2-1T1L

Part number: 8034963

**FESTO**



[PDF](#) General operating condition

## Data sheet

| Feature                                               | Value                                                                     |
|-------------------------------------------------------|---------------------------------------------------------------------------|
| Valve function                                        | 2x3/2-way, open, monostable                                               |
| Type of actuation                                     | Electric                                                                  |
| Construction width                                    | 52 mm                                                                     |
| Standard nominal flow rate (standardised to DIN 1343) | 2400 l/min                                                                |
| pneumatic working port                                | Sub-base size 2 to ISO 5599-2<br>G1/2                                     |
| Operating voltage                                     | 24V DC                                                                    |
| Operating pressure                                    | 0.3 MPa ... 1 MPa                                                         |
| Operating pressure                                    | 3 bar ... 10 bar                                                          |
| Design                                                | Piston gate valve                                                         |
| Approval                                              | c UL us - Recognized (OL)                                                 |
| KC mark                                               | KC-EMV                                                                    |
| CE mark (see declaration of conformity)               | To EU EMC Directive                                                       |
| Degree of protection                                  | IP65<br>NEMA 4                                                            |
| Grid dimension                                        | 59 mm                                                                     |
| Exhaust-air function                                  | With flow control option<br>Via throttle plate<br>Via individual sub-base |
| Sealing principle                                     | Soft                                                                      |
| Mounting position                                     | optional                                                                  |
| Conforms to standard                                  | ISO 5599-2                                                                |
| Manual override                                       | Detenting via accessory<br>Non-detenting                                  |
| Type of piloting                                      | Pilot actuated                                                            |
| Pilot air supply                                      | External                                                                  |
| Flow direction                                        | Non-reversible                                                            |
| Symbol                                                | 00991819                                                                  |
| Signal status display                                 | LED                                                                       |
| Pilot pressure                                        | 0.3 MPa ... 1 MPa                                                         |
| Pilot pressure                                        | 3 bar ... 10 bar                                                          |
| Flow rate of valve                                    | 3000 l/min                                                                |
| Flow rate of valve on individual sub-base             | 2600 l/min                                                                |
| Flow rate of pneumatically interlinked valve          | 2400 l/min                                                                |
| Switching time off                                    | 35 ms                                                                     |
| Switching time on                                     | 20 ms                                                                     |
| Duty cycle                                            | 100%                                                                      |

| Feature                                   | Value                                                                                      |
|-------------------------------------------|--------------------------------------------------------------------------------------------|
| Max. positive test pulse with 0 signal    | 1000 µs                                                                                    |
| Max. negative test pulse with 1 signal    | 3500 µs                                                                                    |
| Nominal pick-up current per solenoid coil | 165 mA up to 30 ms                                                                         |
| Nominal current with current reduction    | 35 mA after 30 ms                                                                          |
| Characteristic coil data                  | 24 V DC: 4.6 W                                                                             |
| Immunity to surge                         | 2.5 kV                                                                                     |
| Pollution degree                          | 3                                                                                          |
| Permissible voltage fluctuations          | +/- 10 %                                                                                   |
| Operating medium                          | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium        | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance                      | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6           |
| Shock resistance                          | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                          |
| Corrosion resistance class CRC            | 0 - No corrosion stress                                                                    |
| LABS (PWIS) conformity                    | VDMA24364-B1/B2-L                                                                          |
| Media temperature                         | -5 °C ... 50 °C                                                                            |
| Relative air humidity                     | 0 - 90%                                                                                    |
| Ambient temperature                       | -5 °C ... 50 °C                                                                            |
| Product weight                            | 740 g                                                                                      |
| Electrical connection                     | Plug-in<br>To ISO 5599-2                                                                   |
| Type of mounting                          | On sub-base                                                                                |
| Pilot air port 12/14                      | Sub-base size 2 to ISO 5599-2                                                              |
| Pilot exhaust port 82/84                  | Ducted<br>Not ducted as per standard<br>Either:                                            |
| Pneumatic connection, port 1              | Sub-base size 2 to ISO 5599-2                                                              |
| Pneumatic connection, port 2              | Sub-base size 2 to ISO 5599-2                                                              |
| Pneumatic connection, port 3              | Sub-base size 2 to ISO 5599-2                                                              |
| Pneumatic connection, port 4              | Sub-base size 2 to ISO 5599-2                                                              |
| Pneumatic connection, port 5              | Sub-base size 2 to ISO 5599-2                                                              |
| Note on materials                         | RoHS-compliant                                                                             |
| Material seals                            | FPM<br>HNBR<br>NBR                                                                         |
| Material housing                          | Die-cast aluminium<br>PA                                                                   |
| Material screws                           | Galvanised steel                                                                           |