



# One-way flow control valve VFOE-LE-T-G14-Q6

Part number: 8068728

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                                                       | Value                                                                                                                      |
|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Valve function                                                                | Exhaust air one-way flow control function                                                                                  |
| Pneumatic connection, port 1                                                  | QS-6                                                                                                                       |
| Pneumatic connection, port 2                                                  | G1/4                                                                                                                       |
| Type of actuation                                                             | Manual                                                                                                                     |
| Adjustment component                                                          | Rotary knob with detent                                                                                                    |
| Type of mounting                                                              | Screw-in                                                                                                                   |
| Standard nominal flow rate in flow control direction                          | 400 l/min                                                                                                                  |
| Standard nominal flow rate in blocked direction                               | 350 l/min ... 450 l/min                                                                                                    |
| Ambient temperature                                                           | -10 °C ... 60 °C                                                                                                           |
| Material housing                                                              | PBT                                                                                                                        |
| Explosion protection                                                          | The information in the certificate must be observed!<br>Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Mounting position                                                             | optional                                                                                                                   |
| Symbol                                                                        | 00991452                                                                                                                   |
| Width across flats                                                            | 16 mm                                                                                                                      |
| Rotatability                                                                  | 360°/no continuous swivelling permissible                                                                                  |
| Operating pressure complete temperature range                                 | 0.02 MPa ... 1 MPa                                                                                                         |
| Operating pressure complete temperature range                                 | 0.2 bar ... 10 bar                                                                                                         |
| Operating pressure complete temperature range                                 | 2.9 psi ... 145 psi                                                                                                        |
| Standard flow rate in flow control direction 0.6-10 MPa (6-10 bar, 87-10 psi) | 610 l/min                                                                                                                  |
| Standard flow rate in non-return direction 0.6-10 MPa (6-10 bar, 87-10 psi)   | 700 l/min ... 800 l/min                                                                                                    |
| Operating medium                                                              | Compressed air to ISO 8573-1:2010 [7:4:4]                                                                                  |
| Note on operating and pilot medium                                            | Lubricated operation possible (in which case lubricated operation will always be required)                                 |
| LABS (PWIS) conformity                                                        | VDMA24364 zone III                                                                                                         |
| Cleanroom class                                                               | Class 4 according to ISO 14644-1                                                                                           |

| Feature                                 | Value            |
|-----------------------------------------|------------------|
| Media temperature                       | -10 °C ... 60 °C |
| Max. tightening torque                  | 12 Nm            |
| Nominal torque                          | 10 Nm            |
| Tolerance for nominal tightening torque | ± 20%            |
| Product weight                          | 16 g             |
| Note on materials                       | RoHS-compliant   |
| Material cover                          | PBT              |
| Material dynamic seals                  | HNBR             |
| Material threaded bolt                  | Galvanised steel |
| Material release ring                   | PBT              |
| Material static seals                   | NBR              |