




Cylinder with holding brake DFLC-40- -

Part number: 8073331

FESTO



 [General operating condition](#)

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	10 mm ... 2000 mm
Piston diameter	40 mm
Piston rod thread	M12x1.25
Based on standard	ISO 15552 (previously also VDMA 24562, ISO 6431, NF E49 003.1, UNI 10290)
Cushioning	Pneumatic cushioning, adjustable at both ends
Mounting position	optional
Type of clamping with direction of action	on both sides Clamping via spring force, released via compressed air
Piston-rod end	Male thread
Design	Piston Piston rod Profile barrel
Position detection	Via proximity switch
Symbol	00995696
Variants	Piston rod at one end
Safety function	Holding and stopping a movement
Performance Level (PL)	Stopping, holding, blocking a movement/category 1, Performance Level c
Operating pressure	0.06 MPa ... 0.8 MPa
Operating pressure	0.6 bar ... 8 bar
Operating pressure	8.7 psi ... 116 psi
Max. permissible test pressure	8 bar
Min. release pressure	3.8 bar
Mode of operation	Double-acting
Approval	German Technical Control Board (TÜV)
CE mark (see declaration of conformity)	To EU Explosion Protection Directive (ATEX) To EC Machinery Directive
UKCA marking (see declaration of conformity)	To UK EX instructions To UK regulations for machines
Explosion protection	Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Certificate issuing authority	German Technical Control Board (TÜV) CA 697
ATEX category gas	II 2G
ATEX category dust	II 2D

Feature	Value
Explosion ignition protection type for gas	Ex h IIC T4 Gb
Explosion ignition protection type for dust	Ex h IIIC T120°C Db
Explosion ambient temperature	-20°C ≤ Ta ≤ +60°C
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Corrosion resistance class CRC	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Ambient temperature	-20 °C ... 80 °C
Cushioning length	19 mm
Static holding force	1350 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke	633 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke	754 N
Moving mass for 0 mm stroke	502 g
Additional moving mass per 10 mm stroke	16 g
Basic weight for 0 mm stroke	2930 g
Additional weight per 10 mm stroke	37 g
Type of mounting	Via female thread With accessories
Release connection, clamping unit	G1/8
Pneumatic connection	G1/4
Note on materials	RoHS-compliant
Material cover	Die-cast aluminium Wrought aluminium alloy
Material seals	NBR TPE-U(PU)
Material housing	Steel
Material piston rod	Steel, hard-chrome-plated
Material cylinder barrel	Smooth-anodised wrought aluminium alloy