



Mini slide DGST-6- -

Part number: 8073891

FESTO



 [General operating condition](#)

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Stroke	10 mm ... 50 mm
Adjustable end position range/length front	6.95 mm ... 13.1 mm
Adjustable end position range/length rear	8.45 mm ... 11.6 mm
Piston diameter	6 mm
Operating mode, drive unit	Yoke
Cushioning	Short elastic cushioning rings/pads at both ends Elastomer cushioning, double-sided, stroke not adjustable Elastic cushioning rings/plates at both ends Elastic cushioning rings/pads at both ends with fixed stop External hydraulic cushioning
Mounting position	optional
Guide	Recirculating ball bearing guide
Design	Twin piston Yoke Piston rod Slide
Position detection	Via proximity switch
Symbol	00991249
Variants	Metals with copper, zinc or nickel by mass as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.
Operating pressure	0.15 MPa ... 0.8 MPa
Operating pressure	1.5 bar ... 8 bar
Operating pressure	21.75 psi ... 116 psi
Max. speed	0.5 m/s
Repetition accuracy	≤ 0.3 mm ≤ 0.02 mm
Mode of operation	Double-acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Corrosion resistance class CRC	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni

Feature	Value
Cleanroom class	Class 6 according to ISO 14644-1
Ambient temperature	-10 °C ... 60 °C
Impact energy in end positions	0.005 J ... 0.1 J
Cushioning length	0.9 mm ... 4 mm
Max. force Fy	200 N ... 280 N
Max. force Fz	200 N ... 280 N
Max. moment Mx	1.1 Nm ... 1.4 Nm
Max. moment My	0.7 Nm ... 1.2 Nm
Max. moment Mz	0.7 Nm ... 1.2 Nm
Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke	25 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke	34 N
Moving mass	49 g ... 93 g
Product weight	90 g ... 182 g
Type of mounting	With through-hole
Pneumatic connection	M3
Note on materials	RoHS-compliant
Material cover	Wrought aluminium alloy
Material seals	HNBR
Material guide	POM TPE-E High-alloy steel
Material housing	Wrought aluminium alloy
Material piston rod	High-alloy stainless steel