Operator unit CDPX-X-E1-W-7 Part number: 8155216

FESTO



General operating condition

Feature	Value
Width	187 mm
Mounting depth	47 mm
Height	147 mm
Length	55 mm
Max. front panel thickness	8 mm
Real-time clock	Yes
Supported PLC protocol	CoDeSys 3.X Modbus RTU client Modbus RTU server Modbus TCP client ModbusTCP server
Deviation, real-time clock	< 100 ppm at 25 °C
Number of colours	16 M
Display	With backlighting
Display type	TFT colour
Display characteristics	Touchscreen
Display size	7"
Backup battery	Rechargeable lithium battery
Operational voltage range DC	10 V 32 V
Display resolution	800x480 pixels
Nominal operating voltage DC	24 V
Current consumption at nominal operating voltage	0.7 A
Approval	c UL us listed (OL)
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
LABS (PWIS) conformity	VDMA24364 zone III
Storage temperature	-20 °C 70 °C
Relative air humidity	5 - 85 % Non-condensing
Degree of protection	IP20 IP66
Note on degree of protection	IP20 rear IP66 front
Ambient temperature	-20 °C 60 °C
Note on ambient temperature	for vertical mounting
Product weight	1300 g

Feature	Value	
SD card slot	1	
Additional functions	RS232 communication function	
Type of mounting	Front panel mounting	
Note on materials	RoHS-compliant	
Ethernet interface, connection type	Socket	
Ethernet interface, connection system	RJ45	
Ethernet interface, number of pins/wires	8	
Ethernet interface, transmission rate	10/100 Mbit/s 1000 Mbps	
Ethernet interface, function	Programming	
Ethernet interface 2, type of connection	2x socket	
Ethernet interface 2, connection technology	RJ45	
Ethernet interface 2, number of pins/wires	8	
Ethernet interface 2, transmission rate	10/100 Mbps	
Ethernet interface 2, function	Programming	
USB interface, function	File transfer	
USB interface, type of connection	2 x socket	
USB interface, connection technology	USB 2.0 type A	
Programming software	Designer Studio	
CPU data	1 GB RAM	