


# Guide unit EAGF-P2-KF-45-50

Part number: 8158131

FESTO



 General operating condition

## Data sheet

| Feature                                               | Value                                |
|-------------------------------------------------------|--------------------------------------|
| Size                                                  | 45                                   |
| Stroke                                                | 50 mm                                |
| Reversing backlash theoretical                        | 0 µm                                 |
| Mounting position                                     | optional                             |
| Guide                                                 | Recirculating ball bearing guide     |
| Design                                                | Guidance                             |
| Max. acceleration                                     | 25 m/s <sup>2</sup>                  |
| Max. speed                                            | 1 m/s                                |
| Corrosion resistance class CRC                        | 0 - No corrosion stress              |
| LABS (PWIS) conformity                                | VDMA24364 zone III                   |
| Degree of protection                                  | IP40                                 |
| Ambient temperature                                   | 0 °C ... 60 °C                       |
| Max. force Fy                                         | 320 N                                |
| Max. force Fy static                                  | 415 N                                |
| Max. force Fz                                         | 320 N                                |
| Max. force Fz static                                  | 415 N                                |
| Max. moment Mx                                        | 15 Nm                                |
| Max. torque Mx static                                 | 19 Nm                                |
| Max. moment My                                        | 10 Nm                                |
| Max. torque My static                                 | 12 Nm                                |
| Max. moment Mz                                        | 10 Nm                                |
| Max. torque Mz static                                 | 12 Nm                                |
| Displacement force                                    | 2 N                                  |
| Moving mass for 0 mm stroke                           | 342 g                                |
| Basic weight for 0 mm stroke                          | 1037 g                               |
| Additional weight per 10 mm stroke                    | 12.3 g                               |
| Additional moving mass per 10 mm stroke               | 12.3 g                               |
| Centre of gravity at 0 mm stroke                      | 25 mm                                |
| Centre of gravity additional of moving mass per 10 mm | 4.3 mm                               |
| Type of mounting                                      | Via female thread                    |
| Note on materials                                     | RoHS-compliant                       |
| Material guide component                              | Tempered steel<br>Hard-chrome-plated |
| Material housing                                      | Anodised                             |
| Material yoke plate                                   | Wrought aluminium alloy<br>Anodised  |