



# Solenoid valve VUVG-LK10-T32C-AT-M5-1H2L-F1A

Part number: 8173199

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                               | Value                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Valve function                                        | 2x3/2-way, monostable, closed                                                              |
| Type of actuation                                     | Electric                                                                                   |
| Valve size                                            | 10 mm                                                                                      |
| Standard nominal flow rate (standardised to DIN 1343) | 180 l/min                                                                                  |
| pneumatic working port                                | M5                                                                                         |
| Operating voltage                                     | 24V DC                                                                                     |
| Operating pressure                                    | 0.15 MPa ... 0.7 MPa                                                                       |
| Operating pressure                                    | 1.5 bar ... 7 bar                                                                          |
| Design                                                | Piston slide with sealing ring                                                             |
| Type of reset                                         | Pneumatic spring                                                                           |
| Approval                                              | c UL us - Recognized (OL)                                                                  |
| Certificate issuing authority                         | UL MH19482                                                                                 |
| Degree of protection                                  | IP40                                                                                       |
| Exhaust-air function                                  | With flow control option                                                                   |
| Sealing principle                                     | Soft                                                                                       |
| Mounting position                                     | optional                                                                                   |
| Manual override                                       | Detenting<br>Non-detenting                                                                 |
| Type of piloting                                      | Pilot actuated                                                                             |
| Pilot air supply                                      | Internal                                                                                   |
| Flow direction                                        | Non-reversible                                                                             |
| Symbol                                                | 00992904                                                                                   |
| lap                                                   | Overlap                                                                                    |
| Signal status display                                 | LED                                                                                        |
| Max. switching frequency                              | 2 Hz                                                                                       |
| Switching time off                                    | 14 ms                                                                                      |
| Switching time on                                     | 12 ms                                                                                      |
| Duty cycle                                            | 100%                                                                                       |
| Max. positive test pulse with 0 signal                | 1600 µs                                                                                    |
| Max. negative test pulse with 1 signal                | 3000 µs                                                                                    |
| Characteristic coil data                              | 24 V DC: 0.8 W                                                                             |
| Permissible voltage fluctuations                      | +/- 10 %                                                                                   |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required) |

| Feature                                            | Value                                                                                                                                                    |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Vibration resistance                               | Transport application test with severity level 1 to FN 942017-4 and EN 60068-2-6                                                                         |
| Shock resistance                                   | Shock test with severity level 1 to FN 942017-5 and EN 60068-2-27                                                                                        |
| Corrosion resistance class CRC                     | 0 - No corrosion stress                                                                                                                                  |
| LABS (PWIS) conformity                             | VDMA24364 zone III                                                                                                                                       |
| Suitability for the production of Li-ion batteries | Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni |
| Cleanroom class                                    | Class 6 according to ISO 14644-1                                                                                                                         |
| Media temperature                                  | -5 °C ... 50 °C                                                                                                                                          |
| Pilot medium                                       | Compressed air to ISO 8573-1:2010 [7:4:4]                                                                                                                |
| Ambient temperature                                | -5 °C ... 50 °C                                                                                                                                          |
| Product weight                                     | 55 g                                                                                                                                                     |
| Electrical connection                              | 2-pin<br>Plug pattern H, horizontal connection<br>Plugs                                                                                                  |
| Type of mounting                                   | Either:<br>On manifold rail<br>With through-hole                                                                                                         |
| Pneumatic connection, port 2                       | M5                                                                                                                                                       |
| Pneumatic connection, port 4                       | M5                                                                                                                                                       |
| Note on materials                                  | RoHS-compliant                                                                                                                                           |
| Material seals                                     | HNBR<br>NBR                                                                                                                                              |
| Material housing                                   | Wrought aluminium alloy                                                                                                                                  |