


Shock absorber DYSD-Q13-4-4-Y1F-Y9

Part number: 8199038

FESTO



 General operating condition

Data sheet

Feature	Value
Size	4
Stroke	4 mm
Cushioning	Self-adjusting
Mounting position	optional
Position detection	Without
Symbol	00991495
Max. impact speed	0.5 m/s
Reset time at room temperature	0.2 s
Reset time at min. ambient temperature	1 s
Mode of operation	Pushing Single-acting
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni
Ambient temperature	-10 °C ... 60 °C
Cushioning length	4 mm
Max. stop force	110 N
Max. tightening torque	1 Nm
Max. energy consumption per stroke	0.6 J
Max. energy consumption per hour	1440 J
Reset force	3 N
Min. insertion force	18 N
Product weight	6.5 g
Load range	4.8 kg
Type of mounting	Via lock nut
Note on materials	RoHS-compliant
Material seals	NBR
Material housing	High-alloy steel
Material piston rod	High-alloy steel
Material nut	High-alloy steel